



SECTION 096566 --- RESILIENT ATHLETIC FLOORING

PART 1-GENERAL

1.1 DESCRIPTION

- A. This document specifies the complete installation of a rubber surface system designed for multiple sport use, as formulated by Wood Floors India Flooring Company.
- B. The concrete contractor shall provide a concrete slab, smooth troweled and level to a tolerance of 1/8" (3mm) in a 10'0" (3m) radius, subject to the approval of the flooring contractor. LABOR AND MATERIALS NECESSARY TO PUT THE CONCRETE SLAB IN ACCEPTABLE CONDITION (HIGH AREAS GROUND DOWN AND LOW AREAS FILLED WITH APPROVED LEVELING COMPOUNDS) SHALL BE THE RESPONSIBILITY OF THE CONCRETE CONTRACTOR.
 - 1. Membrane waterproofing
 - a. Concrete subfloors on or below grade shall be adequately waterproofed beneath and at the perimeter walls and on earth side of below grade walls. It is the responsibility of the engineer to determine the extent of this need.
 - 2. Concrete subfloors shall have an adequate vapor retarder beneath and at the perimeter of the slab.
 - 3. No pea gravel, river gravel or slag aggregate shall be allowed in the concrete. The concrete strength range at the time of wood flooring installation shall be between 3,000 PSI and 3,500 PSI.

1.2 QUALITY ASSURANCE

- A. Supplier Qualifications
 - 1. Supplier of flooring shall be Wood Floors India Flooring Company.
 - 2. Basis of design shall be "EcoTuff" sports floor system as provided by Wood Floors India Flooring, www.WoodFloorsIndiaflooring.com, (800-380-0119).
 - 3. Materials other than those listed must be approved 10 days prior to bid date by written addendum. Materials from non-approved manufacturers will not be accepted.
- B. Installer Qualifications
 - 1. The flooring contractor shall be a Wood Floors India Accredited Installation Company on-site for the duration of the wood floor installation; or, a contractor approved by Wood Floors India Flooring.
- C. Flooring materials shall never be stored outdoors or exposed to outdoor elements in transport or storage.

1.3 WORKING CONDITIONS

- A. The floor system shall not be delivered or installed until the concrete slab is properly cured and all masonry, plastering, tile work and overhead mechanical trades are completed and building is permanently enclosed and weathertight.
- B. Flooring installation shall not begin until all sub-contract work which would cause damage, dirt, dust or interruption of normal installation pace is completed. Subfloors shall be clean, dry and free from dirt, dust, oil, grease, paint, alkali, concrete curing agents, hardening and parting compounds, old adhesive residue, or other foreign materials.
- C. Moisture content of the concrete slab must not exceed 3 pounds per 1,000 square feet (1kg per 68 m²) over 24 hours when using the calcium chloride test as per ASTM 1869-98.
- D. The installation area shall be closed to all traffic and activity for a period to be set by the flooring contractor.
- E. Permanent heat, light, and ventilation shall be installed and operating prior to, during and after installation. HVAC System shall be operating in balance at levels and conditions consistent with those during permanent occupancy.
- F. If the material is to be stored prior to installation, the general contractor shall provide an area where the stored materials can be maintained at a minimum of 55° F (13° C) and relative humidity under 50%.
- G. One week prior to, during and for 168 hours after installation, a room temperature of 65° F (18° C) or more and 35% relative humidity or less shall be maintained.
- H. Adhere to all MSDS requirements for materials employed in the work. Protect all persons from exposure to hazardous materials.



WOOD FLOORS INDIA ECOTUFF SYSTEM

Page 2 of 3

- I. After synthetic floors have been fully installed, the floor area is to be kept locked by general contractor for a minimum of 120 hours to allow curing time for system. No other trades or personnel are allowed on floor until accepted by the owner in writing.

1.4 WARRANTY

- A. Wood Floors India Flooring Company hereby warrants the flooring materials to be free from manufacturing defects for a period of 1 year from the date of substantial completion. This warranty is expressly limited to the flooring materials supplied by Wood Floors India. This warranty is in lieu of all other warranties, expressed or implied including but not limited to any warranty of merchantability or fitness for a particular purpose, and of any other obligations on the part of Wood Floors India. This warranty does not cover floor damage caused by conditions beyond our control, such as fire, wind, floor surface chemical action, faulty maintenance, improper ventilation, faulty construction of building, Act of God, ordinary wear and tear, excess moisture and excess dryness, separation of concrete slab, settlement of walls, failure of floor if not installed properly, when installed over poured urethane or other previously existing floors if poured urethane returns to its liquid state, if previously existing floors release from concrete slab. In the event of breach of any warranty, the liability of Wood Floors India shall be limited to repairing or replacing material and system components supplied by Wood Floors India and proven to be defective in manufacture, and shall not include any other damages, either direct or consequential.
- B. Extended warranties are based on maintenance and yearly/annual cleaning and recoating agreements with certified contractors.

PART 2-PRODUCTS

2.1 MATERIAL

- A. All components shall be non-hazardous and not contain ANY lead, mercury, nor any heavy metals, PCB, or formaldehyde and shall be supplied by Wood Floors India Flooring Company.
- B. Wood Floors India EcoTuff Polyurethane Adhesive.
- C. Wood Floors India EcoTuff Flooring is a recycled rubber product combined from quality recycled SBR tire rubber and recycled EPDM flecks that is a single-ply, non-laminated product with high slip resistance, durability, cushioned resilience and stain resistant.
 1. Rolls
 - a. Thickness: 3/8" (9mm)
 - b. Width: 48" (1219mm)
 - c. Length: To be specified
 2. Tiles
 - a. Thickness: 3/8" (9mm)
 - b. Width: 36" (914mm)
 - c. Length: 36" (914mm)
 3. Invisilock Tiles
 - a. Thickness: 3/8" (9mm)
 - b. Width: 24" (611mm)
 - c. Length: 24" (611mm)
 4. Physical Properties
 - a. Weight: 1.5 lbs/sf (6.1 kgs/sm)
 - b. Color: Available in five standard colors, some color limitations apply to Invisilock product.
 - c. Tensile Strength: 200 lbs/square inch ASTM D412
 - d. Flexibility 1/4" Mandrel: Pass ASTM F137
 - e. Static Load 1000 lbs/square inch: < 0.020 inches ASTM F970
 - f. Coefficient of Friction: >0.9
 - g. Chemical Resistance: ASTM 2047
 1. 5% Acetic Acid: No Change
 2. 70% Isopropyl Alcohol: No Change
 3. 5% Sodium Hydroxide: No Change
 4. 5% Hydrochloric Acid: No Change
 5. 5% Ammonia: No Change



WOOD FLOORS INDIA ECOTUFF SYSTEM

Page 3 of 3

6. 5% Phenol: No Change
 7. Bleach: No Change
 8. Sulfuric Acid: No Change
 - h. Ambient Noise Reduction, Sabin/ft²: 0.10 ASTM C423
 - i. Thermal Conductivity, BTU-in/hr-ft²-°F: approximately 0.406 ASTM C518
 - j. Impact Insulation Class: 45 minimum ASTM E492
 - k. Sound Transmission Coefficient: 45 minimum ASTM 413
- D. OPTION: Vinyl wall base 4" (102mm) high; select color: black or brown.

PART 3-EXECUTION

3.1 INSPECTION

- A. Inspect concrete slab for proper tolerance and dryness and report any discrepancies to the general contractor for correction.
- B. The concrete slab shall be cleaned of all debris so flooring contractor will have adequate access to work surface.
- C. All overhead work and wet trades shall be complete in floor work area.
- D. Installer shall document all working conditions provided in general specifications before installation begins.

3.2 INSTALLATION

- A. Spread single component urethane adhesive using 1/16" square notched towel. No mixing needed.
- B. Install EcoTuff rolls keeping seems tight and bricking as necessary.
- C. OPTION: Install EcoTuff tiles in a "four corner" or "brick" pattern with Wood Floors India single component urethane adhesive using 1/16" square notched towel. No mixing needed.
- D. OPTION: Install EcoTuff Invisilock using no adhesive. Insure that "grain" of tiles is in the same direction. For open ended sides, use appropriate corner and end Invisilock pieces, securing open sides with anchored "Snap Track", high-durometer rubber reducer.

3.3 VINYL WALL BASE - OPTION

- A. Install Vent Cove Base, mitering inside corners and anchoring to walls with base cement or screws and anchors.

3.4 PROTECTION

- A. No traffic or other trades shall be allowed on the surface for a period of one week (168 hours) following installation to allow for complete curing of the finish.
- B. No smoking, open flames, or sparks from electrical equipment or other sources shall be permitted during application of materials

3.5 MAINTENANCE

- A. Upon completion of floor installation, the owner, attendants or individuals in charge and responsible for the upkeep of the building are to see that the care and maintenance instructions outlined within the provided Wood Floors India Care and Maintenance Manual are followed. Wood Floors India Flooring and certified dealers may offer extended warranty and maintenance agreements. It is recommended that any extended agreements include maintenance and recoats by the original installing contractor or related/recommended parties. (See maintenance/cleaning and recoating information on Wood Floors India Flooring website).

END OF SECTION